

SUNSTREAM TRILIFT™

The Sunstream TriLift™ is specifically designed to lift today's premium pontoons/tritoons. Based on Sunstream SunLift™ patented technology, the Sunstream TriLift™ offers premium high-speed, remote-controlled lifting while addressing the unique lifting needs of today's premium pontoons and tritoons. The Sunstream TriLift™ features elongated 17 ft bunks to provide optimal hull support that both minimizes stresses on the hull and evenly distributes weight on the pontoons to provide superior stability. Composite/aluminum bunks offer premium cushioning and protection for the pontoons and are designed to resist wear, scratch and mold. Like other Sunstream products, every detail has been carefully engineered for superior performance, aesthetics, reliability and long life.

DURABLE CONSTRUCTION

- Designed for today's pontoon & tritoons
- Longer frame provides added stability on lift
- Extended bunks delivers greater bunk support
- Constructed from thick marine grade aluminum 6061-T6
- All stainless steel hardware

DESIGNED FOR EASY USE


- Water-resistant transmitters and advanced remote controls technology
- DockEase™ technology with reinforced vertical guide-ons, rolling cushioning tubes and canted bunks makes docking a breeze
- Underhung bunk support beams reduces required water depth by 6"

SAFE & RELIABLE

- Composite bunks are durable and soft for hull support and protection
- Patented Over-center GavityLock™ designed to keep boat up with no cables to break
- SunFluid™ - Environmentally-friendly, water soluble hydraulic fluid
- Fast & smooth remote controlled hydraulics

ACCESSORIES:

- Solar or AC charging
- SwiftShield™ Automatic Boat Cover
- Canopies
- Guide-on pads
- Underwater LED lights
- Bunk risers (for TriToons with larger center hull)
- Leg mounted Powerpack shelf
- Dock mounted Powerpack shelf
- Range extension kits



TECHNICAL SPECIFICATIONS

Item Number	SL7017PAR
Capacity at Standard Range	6,600 lbs
Bunk Length	17 ft
Frame length	14.5 ft
Lifting Range	4 ft range standard
Optional Ranges:	3 ft or 5 ft with SA-EX12*
Capacity at max range (5')	5,500 lbs

*Requires deck crossbeams to be mounted on top of channel bunk

THE ORIGINAL PREMIUM FREESTANDING HYDRAULIC BOAT LIFT



SUNSTREAMCORP.COM